

FTM



### Description

**FTM:** pocket filter with synthetic filtering media  
 • galvanised steel frame

### Accessories

**CF100:** counterframe for frame th. 25, 50, 75 mm and/or combinations

### Technical specifications

Filtration class				
EN 779 / 2012	EN ISO 16890	ePM 1	ePM 2.5	ePM 10
M6	ePM10 70%	10%-40%	20%-50%	60%-80%
F7	ePM1 55%	40%-65%	65%-75%	80%-90%
F8	ePM1 70 %	65%-90%	75%-95%	90%-100%
F9	ePM1 85 %	80%-90%	85%-95%	90-100%

All prices are list prices for local market, for a quotation please contact us.

### Aeraulic specifications and price list

Efficiency	Class	Type	L x H x D mm	Filter surface m <sup>2</sup>	Flow rate m <sup>3</sup> /h	Initial Δpt Pa	€
65%	M6	FTM6158	592x592x535	5.1	2800	110	92
65%	M6	FTM6254	287x592x535	2.5	1400	110	48
65%	M6	FTM6150	592x592x535	6.4	3400	110	112
65%	M6	FTM6255	287x592x535	3.2	1700	110	59
65%	M6	FTM6168	592x592x635	6.0	2800	100	100
65%	M6	FTM6264	287x592x635	2.9	1400	100	53
65%	M6	FTM6160	592x592x635	7.5	3400	100	123
65%	M6	FTM6265	287x592x635	3.7	1700	100	65
85%	F7	FTM7158	592x592x535	5.1	2800	130	95
85%	F7	FTM7254	287x592x535	2.5	1400	130	55
85%	F7	FTM7150	592x592x535	6.4	3400	130	116
85%	F7	FTM7255	287x592x535	3.2	1700	130	65
85%	F7	FTM7168	592x592x635	6.0	2800	110	107
85%	F7	FTM7264	287x592x635	2.9	1400	110	60
85%	F7	FTM7160	592x592x635	7.5	3400	110	130
85%	F7	FTM7265	287x592x635	3.7	1700	110	72
95%	F9	FTM9158	592x592x535	5.1	2800	150	107
95%	F9	FTM9254	287x592x535	2.5	1400	150	62
95%	F9	FTM9150	592x592x535	6.4	3400	150	131
95%	F9	FTM9255	287x592x535	3.2	1700	150	74
95%	F9	FTM9168	592x592x635	6.0	2800	130	119
95%	F9	FTM9264	287x592x635	2.9	1400	130	69
95%	F9	FTM9160	592x592x635	7.5	3400	130	147
95%	F9	FTM9265	287x592x635	3.7	1700	130	82

**CF100** 287x592 €28

**CF100** 592x592 €36

Delivery: 2 weeks

# Rigid pocket filters

FTR



### Description

**FTR:** rigid pocket filter with micro fibreglass filtering media  
 • non-toxic moulded plastic frame, incinerable

### Accessories

**Cf130:** galvanised steel counterframe

### Technical specifications

Filtration class				
EN 779 / 2012	EN ISO 16890	ePM 1	ePM 2.5	ePM 10
M6	ePM10 70%	10%-40%	20%-50%	60%-80%
F7	ePM1 55%	40%-65%	65%-75%	80%-90%
F8	ePM1 70 %	65%-90%	75%-95%	90%-100%
F9	ePM1 85 %	80%-90%	85%-95%	90-100%

All prices are list prices for local market, for a quotation please contact us.

### Aeraulic specifications and price list

Efficiency	Class	Type	L x H x D mm	Filter surface m <sup>2</sup>	Flow rate m <sup>3</sup> /h	Initial Δpt Pa	€
65%	M6	FTR61	592x592x292	18	5000	130	171
65%	M6	FTR62	592x287x292	7.5	2300	130	124
65%	M6	FTR63	592x490x292	13	4100	130	148
85%	F7	FTR71	592x592x292	18	5000	150	177
85%	F7	FTR72	592x287x292	7.5	2300	150	127
85%	F7	FTR73	592x490x292	13	4100	150	154
95%	F8	FTR81	592x592x292	18	5000	160	178
95%	F8	FTR82	592x287x292	7.5	2300	160	128
95%	F8	FTR83	592x490x292	13	4100	160	154
98%	F9	FTR91	592x592x292	18	5000	220	248
98%	F9	FTR92	592x287x292	7.5	2300	220	154
98%	F9	FTR93	592x490x292	13	4100	220	184

**CF130** 592x592 €38

**CF130** 592x287 € 31

**CF130** 592x490 € 37

Delivery: 2 weeks

### Example of order

N. 25      FTR      8      1

Quantity

Rigid pocket filters

Efficiency 95% / F8

Dimension 592x592x292